REMARKS

Upon entry of the present amendment claims 1-14 are pending in the application. Claims 1-14 have been amended in accordance with the requirements of U.S. patent practice. Applicants respectfully request entry of the preliminary amendment.

MARKED UP COPY OF THE AMENDMENTS

IN THE SPECIFICATION

After the title, please insert -- This application is a National Phase Application of Patent Application **PCT/EP00/03267** filed on 12 April 2000--

IN THE CLAIMS:

Please substitute claims 1-14 as follows.

- 1. (Amended) A highly scratch-resistant multicoat clearcoat system A for a primed or unprimed substrate, [producible]produced by
 - (1) applying at least one clearcoat film I of a coating material I curable thermally and with actinic radiation to the surface of the substrate, and partially curing it, [and]
 - (2) applying a further clearcoat film II of a coating material II comprising nanoparticles and curable with actinic radiation and [also, if desired,]optionally thermally, [comprising nanoparticles,]to the surface of the clearcoat film[(s)] I, and [then]
 - (3) curing the clearcoat films I and II conjointly with actinic radiation and thermally.
- (Amended) A highly scratch-resistant multicoat clearcoat system A for a primed or unprimed substrate, [producible]produced by
 - (1) applying at least one clearcoat film I of a coating material I curable thermally and with actinic radiation to the surface of the substrate, curing it and roughening it,

- (2) applying a further clearcoat film II of a coating material II comprising nanoparticles and curable with actinic radiation and [also, if desired,]optionally, thermally, [comprising nanoparticles,]to the outer surface of the clearcoat film[(s)] I, and [then]
- (3) curing the clearcoat film II with actinic radiation and, [if desired]optionally, thermally.
- (Amended) A highly scratch-resistant, multicoat color and/or effect coating system B for a primed or unprimed substrate, [producible]produced by
 - (1) applying at least one color and/or effect basecoat film III of a pigmented coating material III curable thermally and[also], [if desired]optionally, with actinic radiation, to the surface of the substrate and drying it without curing,
 - (2) applying at least one clearcoat film I of a coating material I curable thermally and with actinic radiation wet-on-wet to the surface of the basecoat film III, and partially curing them, [and]
 - (3) applying a further clearcoat film II of a coating material II comprising nanoparticles and curable with actinic radiation and[also], [if desired]optionally, thermally, [comprising nanoparticles,]to the surface of the clearcoat film[(s)] I, and [then]
 - (4) curing the basecoat film(s) III and the clearcoat films I and II conjointly with actinic radiation and thermally.
- 4. (Amended) A highly scratch-resistant multicoat color and/or effect coating system B for a primed or unprimed substrate, [producible]made by
 - (1) applying at least one color and/or effect basecoat film III of a pigmented coating material III curable thermally and[also], [if desired]optionally, with actinic radiation to the surface of the substrate and drying it without curing,

- (2) applying at least one clearcoat film I of a coating material I curable thermally and with actinic radiation wet-on-wet to the surface of the basecoat film III,
- (3) curing the basecoat film III and clearcoat film(s) I conjointly, thermally and with actinic radiation,
- (4) roughening the outer surface of the clearcoat film(s) I,
- (5) applying a further clearcoat film II of a coating material II comprising nanoparticles and curable with actinic radiation and[also], [if desired]optionally[,] thermally, [comprising nanoparticles,] to the outer surface of the clearcoat film[(s)] I, and [then]
- (6) curing the clearcoat film II with actinic radiation and, [if desired]optionally, thermally.
- (Amended) A process for producing a highly scratch-resistant multicoat clearcoat system (A) on a primed or unprimed substrate, [which comprises]comprising
 - (1) applying at least one clearcoat film I of a coating material I curable thermally and with actinic radiation to the surface of [the]a substrate, and partially curing it, and
 - (2) applying a further clearcoat film II of a coating material II comprising nanoparticles and curable with actinic radiation and[also], [if desired,]optionally thermally, [comprising nanoparticles,]to the surface of the clearcoat film[(s)] I, and then
 - (3) curing the clearcoat films I and II conjointly with actinic radiation and thermally.
 - (Amended) A process for producing a highly scratch-resistant multicoat clearcoat system A on a primed or unprimed substrate, [which comprises]comprising

- (1) applying at least one clearcoat film I of a coating material I curable thermally and with actinic radiation to the surface of [the]a substrate, curing it and roughening it,
- (2) applying a further clearcoat film II of a coating material II comprising nanoparticles and curable with actinic radiation and[also], [if desired,]optionally thermally, [comprising nanoparticles,] to the outer surface of the clearcoat film(s) I, and [then]
- (3) curing the clearcoat film II with actinic radiation and, [if desired,]optionally thermally.
- (Amended) A process for producing a highly scratch-resistant multicoat color and/or effect coating system B on a primed or unprimed substrate, [which comprises]comprising
 - (1) applying at least one color and/or effect basecoat film III of a pigmented coating material III curable thermally and[also], [if desired]optionally, with actinic radiation to the surface of the substrate and drying it without curing,
 - (2) applying at least one clearcoat film I of a coating material I curable thermally and with actinic radiation wet-on-wet to the surface of the basecoat film III, and partially curing them, [and]
 - (3) applying a further clearcoat film II of a coating material II comprising nanoparticles and curable with actinic radiation and[also], [if desired]optionally, thermally, [comprising nanoparticles,]to the surface of the clearcoat film[(s)] I, and [then]
 - (4) curing the basecoat film(s) III and the clearcoat films I and II conjointly with actinic radiation and thermally.

- 8. (Amended) A process for producing a highly scratch-resistant multicoat color and/or effect coating system B on a primed or unprimed substrate, [which comprises]comprising
 - (1) applying at least one color and/or effect basecoat film III of a pigmented coating material III curable thermally and[also], [if desired]optionally, with actinic radiation to the surface of the substrate and drying it without curing,
 - (2) applying at least one clearcoat film I of a coating material I curable thermally and with actinic radiation wet-on-wet to the surface of the basecoat film III,
 - (3) curing the basecoat film III and clearcoat film[(s)] I conjointly, thermally and with actinic radiation,
 - (4) roughening the outer surface of the clearcoat film[(s)] I,
 - (5) applying a further clearcoat film II of a coating material II comprising nanoparticles and curable with actinic radiation and[also], [if desired]optionally, thermally, [comprising nanoparticles,]to the outer surface of the clearcoat film[(s)] I, and [then]
 - (6) curing the clearcoat film II with actinic radiation and, [if desired]optionally, thermally.
 - 9. (Amended) The clearcoat system A [as claimed in]of claim 1[or 2],[the multicoat system B as claimed in claim 3 or 4, the process for producing the clearcoat system A as claimed in claim 5 or 6, or the process for producing the multicoat system B as claimed in claim 7 or 8,] wherein the coating material II comprises nanoparticles based on silicon dioxide, aluminum oxide and zirconium oxide.
 - 10. (Amended) The clearcoat system A [as claimed in any]of claim[s] 1[, 2 and 9, the multicoat system B as claimed in any of claims 3, 4 and 9, the process

for producing the clearcoat system A as claimed in any of claims 5, 6 and 9, or the process for producing the multicoat system B as claimed in any of claims 7 to 9,] wherein the coating material I comprises

- (a1) at least one constituent [containing]comprising
 - (a11) at least two functional groups which serve for crosslinking with actinic radiation, and [if desired] optionally
 - (a12) at least one functional group which is able to undergo thermal crosslinking reactions with a complementary functional group (a22) in the constituent (a2), and
- (a2) at least one constituent [containing]comprising
 - (a21) at least two functional groups which serve for crosslinking with actinic radiation, and
 - (a22) at least one functional group which is able to undergothermal crosslinking reactions with a complementary functional group(a12) in the constituent (a1), and [also, if desired]optionally,

one or more members selected from the group consisting of

- (a3) at least one photoinitiator,
- (a4) at least one thermal crosslinking initiator,
- (a5) at least one reactive diluent curable thermally and/or with actinic radiation,
- (a6) at least one coatings additive, [and/or]
- (a7) at least one thermally curable constituent, and mixtures thereof, with the proviso that the coating material I comprises at least one thermally curable constituent (a7) if the constituent (a1) contains no functional group (a12).
- 11. (Amended) The clearcoat system A[, the multicoat system B, the process for producing the clearcoat system A or the process for producing a multicoat system B as claimed in] of claim 10, wherein the functional groups (a11) and

(a21) comprise olefinically unsaturated groups or epoxide groups, [especially olefinically unsaturated groups, hydroxyl groups in the case of the functional groups (a12) and [lacuna] in the case of the complementary functional groups (a22) and isocyanate groups].

- 12. (Amended) The clearcoat system A[, the multicoat system B, the process for producing the clearcoat system A or the process for producing a multicoat system B as claimed in]of claim 10[or 11], wherein the constituent (a1) comprises a urethane (meth)-acrylate and the constituent (a2) comprises a member selected from the group consisting of(meth)acrylate-functional (meth)acrylate copolymer containing free isocyanate groups, [and/or comprises a](meth)acrylate-functional polyisocyanate, and mixtures thereof.
- 13. (Amended) The [use of the clearcoat system A as claimed in any of claims 1, 2 and 9 to 12, of the multicoat systems B as claimed in any of claims 3, 4 and 9 to 12, of the]process [for producing the clearcoat system A as claimed in any]of claim[s] 5, [6 and 9 to 12, or of the process for producing the multicoat system B as claimed in any of claims 7 to 12, in]wherein the substrate is selected from the group consisting of automotive OEM [finishing]substrates, automotive refinish substrates, [the coating of]plastics substrates, furniture [coating]substrates, [and industrial coating, including] coil [coating]substrates and container [coating]substrates.
- 14. (Amended) An article selected from the group consisting of motor vehicles, plastic parts, furniture items, [or other part for private or]industrial [use]parts, [including a]coil, [or]and containers, [comprising at least one clearcoat system A as claimed in any of claims 1, 2 and 9 to 12, at least one multicoat system B as claimed in any of claims 3, 4 and 9 to 12, at least one clearcoat system A]produced [with the aid of]by the process [as claimed in any]of claim[s] 5[, 6 and 9 to 12, and/or at least

one multicoat system B produced with the aid of the process as claimed in any of claims 7 to 12].

Respectfully Submitted,

Mary E. Golota

Registration No. 36,814

Date: October 25, 2001 BASF Corporation 26701 Telegraph Road Southfield, Michigan 48034-2442 (248)-948-2020 Customer No. 26922